





## A general model for rectangular footings. Part I: optimal surface

## Marylú García-Galván, Arnulfo Luévanos-Rojas, Sandra López-Chavarría, Manuel Medina-Elizondo & José Benito Rivera-Mendoza

Instituto de Investigaciones Multidisciplinaria, Universidad Autónoma de Coahuila, Torreón, Coahuila, México. marylugarciagalvan@live.com.mx, arnulfol 2007@hotmail.com, sandylopez5@hotmail.com, drmanuelmedina@yahoo.com.mx, benitoriveramendoza@hotmail.com

Received: December 10th, 2021. Received in revised form: April 25th, 2022. Accepted: May 4th, 2022.

#### Abstract

This paper shows a general model of rectangular footings to obtain the soil minimum contact area (optimal surface) that support from 1 to n columns aligned on a longitudinal axis. The proposed model considers that the soil pressure varies linearly. The recently published models have been presented individually to obtain the soil contact area for rectangular isolated footings, rectangular combined footings that support two columns, these models present the equations, but it is not guaranteed to be the minimum area. The present research complies with the models mentioned above (Luévanos-Rojas 2013, 2016) and can be applied to footings that support 3 or more columns, and also the minimum area is guaranteed. Also, numerical problems are shown the soil minimum contact surface for rectangular isolated footings, and rectangular combined footings that support two and three columns (unrestricted on its sides, one side restricted and two opposite sides restricted).

*Keywords*: general model for rectangular footings; optimal surface; rectangular isolated footings; rectangular combined footings; minimum contact area.

# Un modelo general para zapatas rectangulares. Parte I: superficie óptima

#### Resumen

Este trabajo muestra un modelo general de zapatas rectangulares para obtener el área mínima de contacto del suelo (superficie óptima) que soportan de 1 a "*n*" columnas alineadas en un eje longitudinal. El modelo propuesto considera que la presión del suelo varía linealmente. Los modelos recientemente publicados se han presentado individualmente para obtener el área de contacto con el suelo para zapatas aisladas rectangulares, zapatas combinadas rectangulares que soportan dos columnas, estos modelos presentan las ecuaciones, pero no se garantiza que sea el área mínima. La presente investigación cumple con los modelos mencionados anteriormente (Luévanos-Rojas 2013, 2016) y se puede aplicar a zapatas que soportan 3 o más columnas, además se garantiza el área mínima. Además, se muestran problemas numéricos de la superficie mínima de contacto con el suelo para zapatas aisladas rectangulares y zapatas combinadas rectangulares que soportan dos y tres columnas (sin restricciones en sus lados, un lado restringido y dos lados opuestos restringidos).

Palabras clave: modelo general para zapatas rectangulares; superficie óptima; zapatas aisladas rectangulares; zapatas combinadas rectangulares, área mínima de contacto.

#### 1 Introduction

The main purpose of structural design is to obtain the best structural configurations and its member dimensions to support the imposed loads [1].

The traditional dimensioning process for footings takes a long time and the designer generally finishes the process after several iterations. The dimensions are determined from a procedure of successive approximations [2]. The dimensioning of the footings contact surface area on soil is usually done by admitting a linear distribution for the stresses transmitted to the soil. This hypothesis is quite likely in highly consolidated rocky or sandy and clay soils, and not for the latter when both are normally consolidated; in such a case, a parabolic distribution of stresses may be closer to reality [1-3].

The main contributions (Foundation optimization techniques are very popular because they present the best option for both dimensioning and design) on the topic of

How to cite: García-Galván, M., Luévanos-Rojas, A., López-Chavarría, S., Medina-Elizondo, M. and Rivera-Mendoza, J.B., A general model for rectangular footings. Part I: optimal surface.. DYNA, 89(221), pp. 132-141, April - June, 2022.

optimal design of shallow foundations that have been investigated recently are: Wang and Kulhawy [4] developed the economic design optimization of foundations. Chagovén et al. [5] presented a rectangular shallow foundations optimal design and the formulation. Wang [6] developed the reliabilitybased economic design optimization of spread foundation. Kalinli et al. [7] proposed two approaches to obtain the ultimate bearing capacity of the shallow foundations, the first by means the artificial neural networks and the second by the ant colony optimization. Khajehzadeh et al. [8] presented a modified particle swarm optimization for optimum design of spread footing and retaining wall. Khajehzadeh et al. [9] studied the optimal design for shallow foundations by means the gravitational search algorithm. Basudhar et al. [10] developed the optimal cost-analysis and design of circular footings. Rizwan et al. [11] proposed a cost optimization of combined footings using modified complex method of box. Al-Ansari [12] investigated the structural cost of optimized reinforced concrete isolated footing. Khajehzadeh et al. [13] studied the multi-objective optimization of foundation using global-local gravitational search algorithm. Hassaan [14] proposed an optimal design of machinery shallow foundations with sand soils. Nama et al. [15] presented a parameters optimization of geotechnical problem using different optimization algorithm. Camp and Assadollahi [16] developed the CO<sub>2</sub> and cost optimization of reinforced concrete footings subjected to uniaxial uplift. Sahoo and Kumar [17] presented a study for strip and circular shallow foundations on the ultimate bearing capacity by means of the finite elements, limit analysis, and optimization. Rezaei et al. [18] studied the thinwalled shallow foundations bearing capacity: an experimental study by means of the artificial intelligence. Ukritchon and Keawsawasvong [19] proposed a practical method for the optimal design of continuous footing using ant-colony optimization. El-Sakhawy et al. [20] showed an experimental study for the optimization of foundation shapes on soft soil. López-Chavarría et al. [21] presented a mathematical model for dimensioning of square isolated footings using optimization techniques: general case. López-Chavarría et al. [22] investigated the optimal dimensioning for the corner combined footings. Luévanos-Rojas et al. [23] investigated the optimal design for rectangular isolated footings using the real soil pressure. Gandomi and Kashani [24] used the recent swarm intelligence techniques to estimate the construction minimum cost of the shallow foundation. Velázquez-Santillán et al. [25] investigated the numerical experimentation for the optimal design for reinforced concrete rectangular combined footings. Jelusic and Zlender [26] investigated an optimal design of pad footing based on multi-parametric mixed-integer non-linear programming optimization. Malapur et al. [27] investigated an optimization of reinforced concrete column and footings using genetic algorithm. Rawat and Mittal [28] presented an optimization of eccentrically loaded reinforced concrete isolated footings. Nigdeli et al. [29] studied the metaheuristic optimization of reinforced concrete footings. These documents show the models for specific cases such as isolated footings and combined footings.

The mathematical models have been recently studied to obtain the dimensions of the isolated footings of shape: rectangular, square and circular [30-32]. Also the mathematical models have been presented to obtain the dimensions of the combined footings of shape: rectangular, trapezoidal, of strap and T-shaped [33-36]. These documents show the equations to obtain the dimensions of the contact area of the footings on the soil, but it does not guarantee the minimum area of the footings.

Therefore, the review of the literature clearly shows that there is no close relationship with the topic of optimal dimensioning of the contact surface on the soil for rectangular footings from 1 to n columns aligned on a longitudinal axis that is addressed in this paper.

This paper shows a new mathematical model for rectangular footings (general case) to obtain the most economical contact area on the soil (optimal surface) supporting from 1 to *n* columns aligned on a longitudinal axis (X axis), and each column subject to an axial load and two orthogonal bending moments in the connection with the footing. The proposed model considers that the soil pressure varies linearly. Also, numerical problems are shown to obtain the optimal contact surface on the soil for the rectangular isolated footings, and rectangular combined footings that support two and three columns (without restrictions on their sides, with one side restricted and two restricted opposite sides).

#### 2 Formulation of the general model

Fig. 1 shows a rectangular footing that supports n columns aligned on a longitudinal axis (X axis), and each column provides an axial load and two orthogonal bending moments.

Fig. 2 presents the pressure diagram below the rectangular footing, and also the soil pressure in each corner on the footing.

The general equation to obtain the pressure anywhere on the footing due to the soil can be determined by [30-36]:

$$\sigma = \frac{P}{S} + \frac{M_x y}{I_x} + \frac{M_y x}{I_y} \tag{1}$$

where:  $\sigma$  is the soil pressure anywhere on the footing, S is the contact surface of the footing, P is the axial load applied at the center of gravity of the footing,  $M_x$  is the moment around the X axis,  $M_y$  is the moment around the Y axis, x is the distance parallel to the X axis measured from the center of gravity to the point in study, y is the distance parallel to the Y axis measured from the center of gravity to the point in study,  $I_y$  is the moment of inertia around the Y axis, and  $I_x$  is the moment of inertia around the X axis.



Figure 1. Rectangular footing that supports *n* columns. Source: Prepared by the authors.



Figure 2. Pressure diagram below a rectangular footing. Source: Prepared by the authors.

The geometric properties of the contact surface of the rectangular footing with the soil are:

$$S = L_x L_y \tag{2}$$

$$I_x = \frac{L_x L_y^3}{12} \tag{3}$$

$$l_y = \frac{L_y L_x^3}{12} \tag{4}$$

where:  $L_x$  is the distance in X direction of the footing,  $L_y$  is the distance in Y direction of the footing.

Substituting the eq. (2)-(4) into eq. (1) to find the stresses in each corner of the rectangular footing, these are obtained as follows:

$$\sigma_1 = \frac{R}{L_x L_y} + \frac{6M_{xT}}{L_x L_y^2} + \frac{6M_{yT}}{L_x^2 L_y}$$
(5)

$$\sigma_2 = \frac{R}{L_x L_y} + \frac{6M_{xT}}{L_x L_y^2} - \frac{6M_{yT}}{L_x^2 L_y}$$
(6)

$$\sigma_3 = \frac{R}{L_x L_y} - \frac{6M_{xT}}{L_x L_y^2} + \frac{6M_{yT}}{L_x^2 L_y}$$
(7)

$$\sigma_4 = \frac{R}{L_x L_y} - \frac{6M_{xT}}{L_x L_y^2} - \frac{6M_{yT}}{L_x^2 L_y}$$
(8)

where: *R* is the sum of all the axial forces,  $M_{xT}$  is the sum of all the bending moments around the X axis and  $M_{yT}$  is the sum of all the bending moments around the Y axis. These are obtained from the following equations:

$$R = \sum_{i=1}^{n} P_i \tag{9}$$

$$M_{xT} = \sum_{i=1}^{n} M_{xi} \tag{10}$$

$$M_{yT} = \sum_{i=1}^{n} M_{yi} + \sum_{i=1}^{n} P_i \left( \frac{L_x}{2} - L_a - \sum_{j=i-1}^{n=i-1} L_j \right)$$
(11)

The pressure generated by the soil must be equal or greater to zero and less or equal to the soil available allowable load capacity  $\sigma_p$ .

The conditions of the property limit are:

1. There are no restrictions in the sides of the footing:

$$L_a + \sum_{j=1}^{n=i-1} L_j + \frac{c_{2n-1}}{2} \le L_x \tag{12}$$

2. One of the sides of the footing is restricted:

$$\frac{c_1}{2} + \sum_{j=1}^{n=i-1} L_j + \frac{c_{2n-1}}{2} \le L_x \tag{13}$$

3. Two opposite sides of the footing is restricted:

$$\frac{c_1}{2} + \sum_{i=1}^{n=l-1} L_j + \frac{c_{2n-1}}{2} = L_x \tag{14}$$

### 2.1 Optimal surface

The objective function for the minimum surface  $S_{min}$  is:

$$S_{min} = L_x L_y \tag{15}$$

The constraint functions for the minimum surface are:

$$R = \sum_{i=1}^{n} P_i \tag{16}$$

$$M_{xT} = \sum_{i=1}^{n} M_{xi} \tag{17}$$

$$M_{yT} = \sum_{i=1}^{n} M_{yi} + \sum_{i=1}^{n} P_i \left( \frac{L_x}{2} - L_a - \sum_{j=i-1}^{n=i-1} L_j \right)$$
(18)

$$\sigma_1 = \frac{R}{L_x L_y} + \frac{6M_{xT}}{L_x L_y^2} + \frac{6M_{yT}}{L_x^2 L_y}$$
(19)

$$\sigma_2 = \frac{R}{L_x L_y} + \frac{6M_{xT}}{L_x L_y^2} - \frac{6M_{yT}}{L_x^2 L_y}$$
(20)

$$\sigma_3 = \frac{R}{L_x L_y} - \frac{6M_{xT}}{L_x L_y^2} + \frac{6M_{yT}}{L_x^2 L_y}$$
(21)

$$\sigma_4 = \frac{R}{L_x L_y} - \frac{6M_{xT}}{L_x L_y^2} - \frac{6M_{yT}}{L_x^2 L_y}$$
(22)

$$0 \le \begin{cases} \sigma_1 \\ \sigma_2 \\ \sigma_3 \\ \sigma_4 \end{cases} \le \sigma_p \tag{23}$$

Unrestricted sides

$$L_a + \sum_{j=1}^{n=l-1} L_j + \frac{c_{2n-1}}{2} \le L_x \tag{24}$$

where:  $L_a \ge c_1/2$ . One side restricted

$$\frac{c_1}{2} + \sum_{j=1}^{n=i-1} L_j + \frac{c_{2n-1}}{2} \le L_x \tag{25}$$

Two opposite sides restricted

$$\frac{c_1}{2} + \sum_{j=1}^{n=i-1} L_j + \frac{c_{2n-1}}{2} = L_x$$
 (26)

#### **3** Numerical problems

Three types of numerical problems are presented below: The first numerical example is for rectangular footings that support a column (rectangular isolated footings). The second numerical example is for rectangular footings that support two columns (rectangular combined footings). The third numerical example is for rectangular footings that support three columns (rectangular combined footings). The Tables present three cases for the dimensioning of the rectangular footings varying the soil available allowable load capacity of " $\sigma p = 250, 200, 150 \text{ kN/m2}$ ", and four types varying the mechanical elements acting on the footing. For cases 2 and 3 the separation between the columns varies from 4 to 7 m. The dimensions of the columns in all cases are of 40x40 cm.

#### 3.1 Example 1

Table 1 shows the axial load and two orthogonal bending moments that act on the footing, the optimal dimensions, and the stresses that are generated in each corner of the rectangular footings that support a column (rectangular isolated footings) (see appendix).

#### 3.2 Example 2

Table 2 shows the axial load and two orthogonal bending moments due to the column 1 and the column 2 that act on the footing, the optimal dimensions, and the stresses that are generated in each corner of the rectangular footings that support two columns without restrictions in sides (rectangular combined footings) (see appendix).

Table 3 shows the axial load and two orthogonal bending moments due to the column 1 and the column 2 that act on the footing, the optimal dimensions, and the stresses that are generated in each corner of the rectangular footings that support two columns with a side restricted (rectangular combined footings) (see appendix).

Table 4 shows the axial load and two orthogonal bending moments due to the column 1 and the column 2 that act on the footing, the optimal dimensions, and the stresses that are generated in each corner of the rectangular footings that support two columns with two opposite sides restricted (rectangular combined footings) (see appendix).

#### 3.3 Example 3

Table 5 shows the axial load and two orthogonal bending moments due to the column 1, column 2 and column 3 that act on the footing, the optimal dimensions, and the stresses that are generated in each corner of the rectangular footings that support three columns without restrictions in sides (rectangular combined footings) (see appendix).

Table 6 shows the axial load and two orthogonal bending moments due to the column 1, column 2 and column 3 that act on the footing, the optimal dimensions, and the stresses that are generated in each corner of the rectangular footings that support three columns with a side restricted (rectangular combined footings) (see appendix).

Table 7 shows the axial load and two orthogonal bending moments due to the column 1, column 2 and column 3 that act on the footing, the optimal dimensions, and the stresses that are generated in each corner of the rectangular footings that support three columns with two opposite sides restricted (rectangular combined footings) (see appendix).

#### 4 Results

In Table 1 is observed the following results: The types 1 and 2 in all the cases, the optimal surface, the dimensions and the stresses in each corner of the footing are equal. For the types 3 and 4, when the soil available allowable load capacity decreases, the optimal surface and the dimensions increase. For the first two types in all cases, it is limited by the minimum stress that is zero. For the last two types in all cases, it is limited by the soil available allowable load capacity.

In Table 2 is showed the results for the rectangular combined footings that support two columns without restrictions in sides: The type 1 in all the cases, the optimal surface, the dimensions and the stresses in each corner of the footing are equal. For the types 2, 3 and 4, when the soil available allowable load capacity decreases, the optimal surface increases. For the first type in all cases and the second type of the case 1, it is limited by the minimum stress that is

zero. For another types, it is limited by the soil available allowable load capacity.

In Table 3 is presented the results for the rectangular combined footings that support two columns with a side restricted: For all types in all cases are presented the same results for the rectangular combined footings that support two columns without restrictions in sides (see Table 1) with the exception of type 4 for the three cases that show different sides of the footing.

In Table 4 is observed the results for the rectangular combined footings that support two columns with two opposite sides restricted: The types 1, 2 and 3 in all the cases, the optimal surface, the dimensions and the stresses in each corner of the footing are equal. For the type 4, when the soil available allowable load capacity decreases, the optimal surface and the dimension  $L_y$  increase, and the dimension  $L_x$  does not change because it is restricted. For the first three types in all cases, it is limited by the minimum stress that is zero. For the last type in all cases, it is limited by the soil available allowable load capacity. Also the resulting moments around the Y axis have a value and these are negative, this means that the resultant forces do not coincide with the center of gravity of the footing.

In Table 5 is showed the results for the rectangular combined footings that support three columns without restrictions in sides: The type 1 in all the cases, the optimal surface, the dimensions and the stresses in each corner of the footing are equal. For the types 2, 3 and 4, when the soil available allowable load capacity decreases, the optimal surface increases. For the first type in all cases and the second type of the case 1, it is limited by the minimum stress that is zero. For another types, it is limited by the soil available allowable load capacity.

In Table 6 is presented the results for the rectangular combined footings that support three columns with a side restricted: For all types in all cases are presented the same results for the rectangular combined footings that support three columns without restrictions in sides (see Table 5) with the exception of type 4 for the case 1 that shows different sides of the footing.

In Table 7 is observed the results for the rectangular combined footings that support three columns with two opposite sides restricted: The types 1 and 2 in all the cases,

the optimal surface, the dimensions and the stresses in each corner of the footing are equal. For the types 3 and 4, when the soil available allowable load capacity decreases, the optimal surface and the dimension  $L_y$  increase, and the dimension  $L_x$  does not change because it is restricted. For the first two types in all cases, it is limited by the minimum stress that is zero. For the last two types in all cases, it is limited by the soil available allowable load capacity. Also the resulting moments around the Y axis have a value and these are negative, this means that the resultant forces do not coincide with the center of gravity of the footing.

Fig. 3 shows the optimal surface of example 1 of the three cases of rectangular footings that support a column (rectangular isolated footings). It is clearly observed that when the moments decrease, the contact surface decreases in all cases.

Fig. 4 shows the optimal surface of the example 2 for rectangular footings that support two columns (rectangular combined footings). The comparison of the optimal surface for sides without restrictions, for a restricted side and for two opposite sides restricted of the same type in each case is observed that the rectangular footings with two opposite sides restricted have greater contact surface with respect to the rectangular footings with a restricted side and sides without restrictions. For the three cases is observed that when the moments decrease, the contact surface decreases in all cases.

Fig. 5 shows the optimal surfaces of the example 3 for rectangular footings that support three columns (rectangular combined footings). The comparison of the optimal surface area for sides without restrictions, for a restricted side and for two opposite sides restricted of the same type in each case is observed that the rectangular footings with two opposite sides restricted have greater contact surface with respect to the rectangular footings with a restricted side and sides without restrictions. For the three cases is observed that when the moments decrease, the contact surface decreases in all cases.

The types 1 and 2 are same for the three cases of the three examples, because the soil pressure is governed by zero pressure, i.e., it does not reach the available permissible load capacity of the soil.



Figure 3. Optimal surfaces for rectangular footings that support a column. Source: Prepared by the authors.



Figure 4. Optimal surfaces for rectangular footings that support two columns. Source: Prepared by the authors.



Figure 5. Optimal surfaces for rectangular footings that support three columns. Source: Prepared by the authors.

#### 5 Conclusions

This paper shows a general model for rectangular footings to obtain the most economical contact area on the soil (optimal surface) that supports from 1 to *n* columns aligned on a longitudinal axis. The proposed model considers that the soil pressure varies linearly.

The models normally used to obtain the dimensions are: the dimensions are proposed and these are verified so that they are within the allowed limits, i.e., the pressure generated by the soil must be equal or greater to zero, and less or equal to the soil available allowable load capacity.

The traditional dimensioning process for footings takes a long time and the designer generally finishes the process after several iterations. The dimensions are determined from a procedure of successive approximations.

The main conclusions are:

- 1. When the moments around of the Y axis are zero, this means that the resultant forces match the center of gravity of the footing (see Tables 2, 3, 5 and 6).
- 2. When the moments around of the Y axis differ from zero, this means that the resultant forces do not match the center of gravity of the footing (see Tables 4 and 7).
- 3. The methodology shown in this document is more precise and converges more quickly with respect to the current model that is based on trial and error.

- 4. The traditional model for footings will not be practical compared with this model, because the traditional model for footings takes a long time and the dimensions are determined from a procedure of successive approximations.
- 5. The proposed model can be used for the dimensioning of rectangular isolated footings (see Table 1).
- 6. The proposed model can be used for the dimensioning of rectangular combined footings that support two or more columns aligned on a longitudinal axis (X axis) for sides without restrictions, a side restricted and two opposite sides restricted. For footings that support two columns (see Tables 2, 3 and 4). For footings that support three columns (see Tables 5, 6 and 7).

The model presented in this paper is effective tool in finding the optimal contact surface of the rectangular footing on soil that support one, two or more columns. This model is generated from of the loads and orthogonal bending moments that provide the columns aligned on a longitudinal axis (X axis).

The proposed expressions directly offer the dimensions of the contact surface of the rectangular footings on soil, also guaranteeing that the admissible stress in the soil will not be exceeded.

The investigations to consider in the future are: 1) Rectangular foundation slabs. 2) Foundations of type "L" of corners for two or more columns aligned on each axis (X and Y axes). 3) Foundations of type "U" for two corners.

## Appendix

### Table 1.

## Dimensions for the rectangular isolated footings that support a column.

Tumo	Mechanio	Mechanical elements acting on the footing			Resulting from forces and moments			Dimensions		Stresses that are generated in each corner of the footing				
Type	Р	Mx	My	R	M <sub>xT</sub>	MyT	-	Lx	Ly	σ1	σ2	σ3	σ4	
	kN	kN	-m	kN	kN	-m	m <sup>2</sup>	I	n		kN	/m <sup>2</sup>		
						Case 1 ( $\sigma_p =$	250.00 kN/r	n²)						
1	600	300	150	600	300	150	18.00	3.00	6.00	66.67	33.33	33.33	0.00	
2	600	200	100	600	200	100	8.00	2.00	4.00	150.00	75.00	75.00	0.00	
3	600	100	50	600	100	50	4.09	1.43	2.86	250.00	147.05	145.05	44.10	
4	600	0	0	600	0	0	2.40	1.55	1.55	250.00	250.00	250.00	250.00	
					(	Case 2 ( $\sigma_p =$	200.00 kN/r	n <sup>2</sup> )						
1	600	300	150	600	300	150	18.00	3.00	6.00	66.67	33.33	33.33	0.00	
2	600	200	100	600	200	100	8.00	2.00	4.00	150.00	75.00	75.00	0.00	
3	600	100	50	600	100	50	4.91	1.57	3.13	200.00	122.10	122.10	44.20	
4	600	0	0	600	0	0	3.00	1.68	1.79	200.00	200.00	200.00	200.00	
					(	Case 3 ( $\sigma_p =$	150.00 kN/r	n²)						
1	600	300	150	600	300	150	18.00	3.00	6.00	66.67	33.33	33.33	0.00	
2	600	200	100	600	200	100	8.00	2.00	4.00	150.00	75.00	75.00	0.00	
3	600	100	50	600	100	50	6.26	1.77	3.54	150.00	95.83	95.83	41.67	
4	600	0	0	600	0	0	4.00	2.07	1.94	150.00	150.00	150.00	150.00	

Source: Prepared by the authors.

 Table 2.

 Dimensions for the rectangular combined footings that support two columns without restrictions in sides.

Mechanical elements acting on the footing					ooting	Resulting from					Dimensions			Stresses that are generated in each				
Trme	С	olumn 1		(	Column	2	forces	and mo	ments	$L_1$	Smin		mensio	115		corner of t	he footing	
Type	Р	Mx	My	Р	Mx	My	R	M <sub>xT</sub>	MyT	-		La	Lx	Ly	$\sigma_1$	$\sigma_2$	σ3	σ4
	kN	kN	l-m	kN	kN	l-m	kN	kN	l-m	m	m <sup>2</sup>		m			kN/	/m <sup>2</sup>	
								Ca	se 1 (σ <sub>p</sub>	= 250.00	kN/m <sup>2</sup> )							
1	600	300	150	1200	600	300	1800	900	0	7.00	27.70	0.20	9.23	3.00	129.96	129.96	0.00	0.00
2	600	200	100	1200	400	200	1800	600	0	6.00	16.13	0.20	8.07	2.00	223.14	223.14	0.00	0.00
3	600	100	50	1200	200	100	1800	300	0	5.00	11.51	0.20	6.90	1.67	250.00	250.00	62.65	62.65
4	600	0	0	1200	0	0	1800	0	0	4.00	7.20	0.38	6.10	1.18	250.00	250.00	250.00	250.00
								Ca	se 2 (op	= 200.00	kN/m <sup>2</sup> )							
1	600	300	150	1200	600	300	1800	900	0	7.00	27.70	0.20	9.23	3.00	129.96	129.96	0.00	0.00
2	600	200	100	1200	400	200	1800	600	0	6.00	17.36	0.20	8.07	2.15	200.00	200.00	7.34	7.34
3	600	100	50	1200	200	100	1800	300	0	5.00	13.57	0.20	6.90	1.97	200.00	200.00	65.20	65.20
4	600	0	0	1200	0	0	1800	0	0	4.00	9.00	1.75	8.82	1.02	200.00	200.00	200.00	200.00
								Ca	se 3 (op	= 150.00	kN/m <sup>2</sup> )							
1	600	300	150	1200	600	300	1800	900	0	7.00	27.70	0.20	9.23	3.00	129.96	129.96	0.00	0.00
2	600	200	100	1200	400	200	1800	600	0	6.00	21.15	0.20	8.07	2.62	150.00	150.00	20.19	20.19
3	600	100	50	1200	200	100	1800	300	0	5.00	16.90	0.20	6.90	2.45	150.00	150.00	63.02	63.02
4	600	0	0	1200	0	0	1800	0	0	4.01	12.00	0.22	5.77	2.08	150.00	150.00	150.00	150.00
~																		

Source: Prepared by the authors.

#### Table 3.

#### Dimensions for the rectangular combined footings that support two columns with a side restricted.

	Mec	hanical	element	s acting o	on the fo	oting	Resulting from forces				D:	naiona	Stresses that are generated in each corner				
Type	(	Column	1	(	Column 2	2	ar	ıd momer	nts	$L_1$	Smin	Dime	iisioiis		of the t	footing	
Type	Р	Mx	My	Р	Mx	My	R	M <sub>xT</sub>	MyT			Lx	Ly	<b>σ</b> 1	σ2	σ3	<b>σ</b> 4
	kN	kN	-m	kN	kN	-m	kN	kN	-m	m	m <sup>2</sup>	I	n		kN	/m <sup>2</sup>	
								Case 1	$\sigma_p = 25$	0.00 kN/ı	n²)						
1	600	300	150	1200	600	300	1800	900	0	7.00	27.70	9.23	3.00	129.96	129.96	0.00	0.00
2	600	200	100	1200	400	200	1800	600	0	6.00	16.13	8.07	2.00	223.14	223.14	0.00	0.00
3	600	100	50	1200	200	100	1800	300	0	5.00	11.51	6.90	1.67	250.00	250.00	62.65	62.65
4	600	0	0	1200	0	0	1800	0	0	4.00	7.20	5.73	1.26	250.00	250.00	250.00	250.00
								Case 2	$2(\sigma_p = 20)$	0.00 kN/ı	n²)						
1	600	300	150	1200	600	300	1800	900	0	7.00	27.70	9.23	3.00	129.96	129.96	0.00	0.00
2	600	200	100	1200	400	200	1800	600	0	6.00	17.36	8.07	2.15	200.00	200.00	7.34	7.34
3	600	100	50	1200	200	100	1800	300	0	5.00	13.57	6.90	1.97	200.00	200.00	65.20	65.20
4	600	0	0	1200	0	0	1800	0	0	4.00	9.00	5.73	1.57	200.00	200.00	200.00	200.00
							Case 3 ( $\sigma_p = 150.00 \text{ kN/m}^2$ )										
1	600	300	150	1200	600	300	1800	900	0	7.00	27.70	9.23	3.00	129.96	129.96	0.00	0.00
2	600	200	100	1200	400	200	1800	600	0	6.00	21.15	8.07	2.62	150.00	150.00	20.19	20.19
3	600	100	50	1200	200	100	1800	300	0	5.00	16.90	6.90	2.45	150.00	150.00	63.02	63.02
4	600	0	0	1200	0	0	1800	0	0	4.00	12.00	5.73	2.09	150.00	150.00	150.00	150.00

Source: Prepared by the authors.

Table 4.	
----------	--

Limensions for the rectangular combined tootings that support two collimps wi	th two opposite sides restricted

	Mech	hanical	element	s acting o	on the fo	ooting	Resul	ting from	forces			Dime	neione	Stresses that are generated in each corner			
Type	(	Column	1	0	olumn 2	2	aı	nd momen	nts	$L_1$	Smin	Dime	11310113		of the	footing	
rype	Р	Mx	My	Р	Mx	My	R	M <sub>xT</sub>	MyT			Lx	Ly	σ1	σ2	σ3	<b>σ</b> 4
	kN	kN	-m	kN	kN	[-m	kN	kľ	N-m	m	m <sup>2</sup>		m		kN	/m <sup>2</sup>	
								Case	$= 1 (\sigma_p = 25)$	0.00 kN/	<sup>'</sup> m <sup>2</sup> )						
1	600	300	150	1200	600	300	1800	900	-1650	7.00	86.46	7.40	11.68	10.69	41.64	0.00	30.95
2	600	200	100	1200	400	200	1800	600	-1500	6.00	58.51	6.40	9.14	13.46	61.52	0.00	48.07
3	600	100	50	1200	200	100	1800	300	-1350	5.00	32.40	5.40	6.00	18.52	111.11	0.00	92.59
4	600	0	0	1200	0	0	1800	0	-1200	4.00	13.75	4.40	3.12	11.90	250.00	11.90	250.00
								Case 2 ( $\sigma_p = 200$			'm²)						
1	600	300	150	1200	600	300	1800	900	-1650	7.00	86.46	7.40	11.68	10.69	41.64	0.00	30.95
2	600	200	100	1200	400	200	1800	600	-1500	6.00	58.51	6.40	9.14	13.46	61.52	0.00	48.07
3	600	100	50	1200	200	100	1800	300	-1350	5.00	32.40	5.40	6.00	18.52	111.11	0.00	92.59
4	600	0	0	1200	0	0	1800	0	-1200	4.00	17.18	4.40	3.90	9.52	200.00	9.52	200.00
							Case 3 ( $\sigma_p = 150.00 \text{ kN/m}^2$ )										
1	600	300	150	1200	600	300	1800	900	-1650	7.00	86.46	7.40	11.68	10.69	41.64	0.00	30.95
2	600	200	100	1200	400	200	1800	600	-1500	6.00	58.51	6.40	9.14	13.46	61.52	0.00	48.07
3	600	100	50	1200	200	100	1800	300	-1350	5.00	32.40	5.40	6.00	18.52	111.11	0.00	92.59
4	600	0	0	1200	0	0	1800	0	-1200	4.00	22.91	4.40	5.21	7.14	150.00	7.14	150.00

Source: Prepared by the authors.

Table 5.

Dimensions for the rectangular combined footings that support three columns without restrictions in sides.

	Mechanical elements acting on the footing				ooting	Resulting from forces			$L_1$		Dimensions			Stresses that are generated				
Туре	(	Column	1	Colu	mn 2 a	nd 3	an	d momer	nts	and	Smin	1	Jimension	15	in e	ach corner	of the foot	ting
	Р	Mx	My	Р	Mx	My	R	M <sub>xT</sub>	MyT	L <sub>2</sub>		La	Lx	Ly	σ1	σ2	σ3	<b>σ</b> 4
	kN	kN	-m	kN	kN	l-m	kN	kN	-m	m	m <sup>2</sup>		m			kN	/m <sup>2</sup>	
								Ca	se 1 (op	= 250.00	0 kN/m²)							
1	600	300	150	1200	600	300	3000	1500	0	7.00	50.10	0.20	16.70	3.00	119.76	119.76	0.00	0.00
2	600	200	100	1200	400	200	3000	1000	0	6.00	28.93	0.20	14.47	2.00	207.37	207.37	0.00	0.00
3	600	100	50	1200	200	100	3000	500	0	5.00	19.52	0.20	12.23	1.60	250.00	250.00	57.37	57.37
4	600	0	0	1200	0	0	3000	0	0	4.00	12.00	0.72	11.05	1.09	250.00	250.00	250.00	250.00
								Case 2 (op			0 kN/m²)							
1	600	300	150	1200	600	300	3000	1500	0	7.00	50.10	0.20	16.70	3.00	119.76	119.76	0.00	0.00
2	600	200	100	1200	400	200	3000	1000	0	6.00	29.64	0.20	14.47	2.05	200.00	200.00	2.42	2.42
3	600	100	50	1200	200	100	3000	500	0	5.00	22.98	0.20	12.23	1.88	200.00	200.00	61.05	61.05
4	600	0	0	1200	0	0	3000	0	0	4.00	15.00	0.20	10.00	1.50	200.00	200.00	200.00	200.00
							Case 3 ( $\sigma_p = 150.00 \text{ kN/m}^2$ )											
1	600	300	150	1200	600	300	3000	1500	0	7.00	50.10	0.20	16.70	3.00	119.76	119.76	0.00	0.00
2	600	200	100	1200	400	200	3000	1000	0	6.00	36.05	0.20	14.47	2.49	150.00	150.00	16.43	16.43
3	600	100	50	1200	200	100	3000	500	0	5.00	28.57	0.20	12.23	2.34	150.00	150.00	60.05	60.05
4	600	0	0	1200	0	0	3000	0	0	4.00	20.00	0.20	10.00	2.00	150.00	150.00	150.00	150.00

Source: Prepared by the authors.

Table 6.

Dimensions for the rectangular combined footings that support three columns with a side restricted.

	Mech	nanical e	element	s acting o	on the fo	ooting	Result	ing from	forces	Liand		Dimen	sions	Stress	es that are	generated i	in each
Туре	(	Column	1	Colu	ımn 2 aı	1d 3	an	d momer	nts	Li anu	Smin	Dimen	510115		corner of	the footing	
	Р	Mx	My	Р	Mx	My	R	M <sub>xT</sub>	MyT	12		Lx	Ly	<b>σ</b> 1	σ2	σ3	<b>σ</b> 4
	kN	kN	-m	kN	kN	-m	kN	kN	-m	m	m <sup>2</sup>	n	1	kN/m <sup>2</sup>			
								Ca	se 1 (σ <sub>p</sub> =	= 250.00 kN/	m <sup>2</sup> )						
1	600	300	150	1200	600	300	3000	1500	0	7.00	50.10	16.70	3.00	119.76	119.76	0.00	0.00
2	600	200	100	1200	400	200	3000	1000	0	6.00	28.93	14.47	2.00	207.37	207.37	0.00	0.00
3	600	100	50	1200	200	100	3000	500	0	5.00	19.52	12.23	1.60	250.00	250.00	57.37	57.37
4	600	0	0	1200	0	0	3000	0	0	4.00	12.00	10.00	1.20	250.00	250.00	250.00	250.00
							Case 2 ( $\sigma_p =$		= 200.00 kN/1	m <sup>2</sup> )							
1	600	300	150	1200	600	300	3000	1500	0	7.00	50.10	16.70	3.00	119.76	119.76	0.00	0.00
2	600	200	100	1200	400	200	3000	1000	0	6.00	29.64	14.47	2.05	200.00	200.00	2.42	2.42
3	600	100	50	1200	200	100	3000	500	0	5.00	22.98	12.23	1.88	200.00	200.00	61.05	61.05
4	600	0	0	1200	0	0	3000	0	0	4.00	15.00	10.00	1.50	200.00	200.00	200.00	200.00
		Case 3							se 3 (o <sub>p</sub> =	= 150.00 kN/1	m <sup>2</sup> )						
1	600	300	150	1200	600	300	3000	1500	0	7.00	50.10	16.70	3.00	119.76	119.76	0.00	0.00
2	600	200	100	1200	400	200	3000	1000	0	6.00	36.05	14.47	2.49	150.00	150.00	16.43	16.43
3	600	100	50	1200	200	100	3000	500	0	5.00	28.57	12.23	2.34	150.00	150.00	60.05	60.05
4	600	0	0	1200	0	0	3000	0	0	4.00	20.00	10.00	2.00	150.00	150.00	150.00	150.00

Source: Prepared by the authors.

Table 7.

Dimensi	ons fo	or the	rectangular	· combined	footings	that support	three co	dumns with	two opposit	e sides res	stricted
Dimentor	0110 10		1	e o mo mea	rootingo	and bappon		i continue of their	ene oppoon	• • • • • • • • • •	

	Mecl	hanical	element	s acting o	on the fo	ooting	Resul	ting from	forces	L <sub>1</sub>		Dimor	sions	Stress	es that are g	enerated i	n each
Туре	(	Column	1	Colu	ımn 2 aı	nd 3	a	nd momei	nts	and	Smin	Dimer	1510115		corner of t	he footing	
	Р	Mx	My	Р	Mx	My	R	M <sub>xT</sub>	MyT	$L_2$		Lx	Ly	$\sigma_1$	σ2	σ3	<b>σ</b> 4
	kN	kN	-m	kN	kN	l-m	kN	kN-m		m	m <sup>2</sup>	n	1		kN/	m <sup>2</sup>	
							$\frac{\text{Case 1} (\sigma_p = 250.00 \text{ kN/m}^2)}{3000}$				m²)						
1	600	300	150	1200	600	300	3000	1500	-3450	7.00	82.94	14.40	5.76	37.68	72.34	0.00	34.66
2	600	200	100	1200	400	200	3000	1000	-3100	6.00	49.60	12.40	4.00	60.48	120.97	0.00	60.48
3	600	100	50	1200	200	100	3000	500	-2750	5.00	23.63	10.40	2.27	115.71	250.00	3.94	138.23
4	600	0	0	1200	0	0	3000	0	-2400	4.00	18.86	8.40	2.24	68.18	250.00	68.18	250.00
	Case 2 ( $\sigma_p = 200$				0.00 kN/i	m²)											
1	600	300	150	1200	600	300	3000	1500	-3450	7.00	82.94	14.40	5.76	37.68	72.34	0.00	34.66
2	600	200	100	1200	400	200	3000	1000	-3100	6.00	49.60	12.40	4.00	60.48	120.97	0.00	60.48
3	600	100	50	1200	200	100	3000	500	-2750	5.00	28.42	10.40	2.73	88.36	200.00	11.11	122.75
4	600	0	0	1200	0	0	3000	0	-2400	4.00	23.57	8.40	2.81	54.55	200.00	54.55	200.00
		Case 3 ( $\sigma_p = 150$						0.00 kN/i	m <sup>2</sup> )								
1	600	300	150	1200	600	300	3000	1500	-3450	7.00	82.94	14.40	5.76	37.68	72.34	0.00	34.66
2	600	200	100	1200	400	200	3000	1000	-3100	6.00	49.60	12.40	4.00	60.48	120.97	0.00	60.48
3	600	100	50	1200	200	100	3000	500	-2750	5.00	36.31	10.40	3.49	62.60	150.00	15.26	102.66
4	600	0	0	1200	0	0	3000	0	-2400	4.00	31.43	8.40	3.74	40.91	150.00	40.91	150.00

Source: Prepared by the authors.

#### References

- [1] Bowles, J.E., Foundation analysis and design, McGraw-Hill, New York, USA, 1996.
- [2] Villalaz, C., Mecánica de suelos y cimentaciones, Limusa, México D.F., México, 2009.
- [3] Luévanos-Rojas, A., A comparative study for dimensioning of footings with respect to the contact surface on soil. International Journal of Innovative Computing, Information and Control, [online]. 10(4), pp. 1313-1326, 2014. Available at: http://www.ijicic.org/ijicic-13-08003.pdf
- [4] Wang, Y. and Kulhawy, F.H., Economic design optimization of foundations. Journal of Geotechnical and Geoenvironmental Engineering, 134(8), pp. 1097-1105, 2008. DOI: https://doi.org/10.1061/(ASCE)1090-0241(2008)134:8(1097)
- [5] Chagoyén, E., Negrín, A., Cabrera, M., López, L. and Padrón, N., Diseño óptimo de cimentaciones superficiales rectangulares. Formulación. Revista de la Construcción, 8(2), pp. 60-71, 2009.
- [6] Wang, Y., Reliability-Based economic design optimization of spread foundation. Journal of Geotechnical and Geoenvironmental Engineering, 135(7), pp. 954-959, 2009. DOI: https://doi.org/10.1061/(ASCE)GT.1943-5606.0000013
- [7] Kalinli, A., Acar, C. and Gündüz, Z., New approaches to determine the ultimate bearing capacity of shallow foundations based on artificial neural networks and ant colony optimization, Engineering Geology, 117(1-2), pp. 29-38, 2011. DOI: https://doi.org/10.1016/j.enggeo.2010.10.002
- [8] Khajehzadeh, M., Taha, M.R., El-Shafie, A. and Eslami, M., Modified particle swarm optimization for optimum design of spread footing and retaining wall. Journal of Zhejiang University-SCIENCE A, 12(6), pp. 415-427, 2011. DOI: https://doi.org/10.1631/jzus.A1000252
- [9] Khajehzadeh, M., Taha, M.R., El-Shafie, A. and Eslami, M., Optimization of shallow foundation using gravitational search algorithm. Research Journal of Applied Sciences Engineering and Technology, 4(9), pp. 1124-1130, 2012.
- [10] Basudhar, P.K., Dey, A. and Mondal, A.S., Optimal cost-analysis and design of circular footings. International Journal of Engineering and Technology Innovation, 2(4), pp. 243-264, 2012. https://doaj.org/article/02a2f16cb4bc4243ade1383eecb7241b
- [11] Rizwan, M., Alam, B., Rehman, F.U., Masud, N., Shahzada, K. and Masud, T., Cost optimization of combined footings using modified complex method of box. International Journal of Advanced Structures and Geotechnical Engineering, 1(1), pp. 24-28, 2012.
- [12] Al-Ansari, M.S., Structural cost of optimized reinforced concrete isolated footing. International Journal of Architectural, Civil and Construction Sciences, 7(4), pp. 304-311, 2013.
- [13] Khajehzadeh, M., Taha, M.R. and Eslami, M., Multi-objective optimization of foundation using global-local gravitational search

algorithm. Structural Engineering and Mechanics, 50(3), pp. 257-273, 2014. DOI: https://doi.org/10.12989/sem.2014.50.3.257

- [14] Hassaan, G.A., Optimal design of machinery shallow foundations with sand soils. International Journal of Research in Engineering and Technology, 3(5), pp. 1-8, 2014.
- [15] Nama, S., Saha, A.K. and Ghosh, S., Parameters optimization of geotechnical problem using different optimization algorithm. Geotechnical and Geological Engineering, 33(5), pp. 1235-1253, 2015. DOI: https://doi.org/10.1007/s10706-015-9898-0
- [16] Camp, Ch.V. and Assadollahi, A., CO<sub>2</sub> and cost optimization of reinforced concrete footings subjected to uniaxial uplift. Journal of Building Engineering, 3, pp. 171-183, 2015. DOI: https://doi.org/10.1016/j.jobe.2015.07.008
- [17] Sahoo, J.P. and Kumar, J., Ultimate bearing capacity of shallow strip and circular foundations by using limit analysis, finite elements, and optimization. International Journal of Geotechnical Engineering, 9 (1), pp. 30-41, 2015. DOI: https://doi.org/10.1179/1939787914Y.0000000070
- [18] Rezaei, H., Nazir, R. and Momeni, E., Bearing capacity of thin-walled shallow foundations: an experimental and artificial intelligence-based study. Journal of Zhejiang University-SCIENCE A, 7(4), pp. 273-285, 2016. DOI: https://doi.org/10.1631/jzus.A1500033
- [19] Ukritchon, B. and Keawsawasvong, S., A practical method for the optimal design of continuous footing using ant-colony optimization. Acta Geotechnica Slovenica, 13(2), pp. 45-55, 2016.
- [20] El-Sakhawy, N.R., Salem, T.N., Al-Tuhamy, A.A. and El-Latief, A.A., Experimental study for the optimization of foundation shapes on soft soil. The Egyptian International Journal of Engineering Sciences and Technology, 21, pp. 24-32, 2016. https://dx.doi.org/10.21608/eijest.2016.97182
- [21] López-Chavarría, S., Luévanos-Rojas, A. and Medina-Elizondo, M., A mathematical model for dimensioning of square isolated footings using optimization techniques: general case. International Journal of Innovative Computing, Information and Control, 13(1), pp. 67-74, 2017. http://www.ijicic.org/ijicic-130105.pdf
- [22] López-Chavarría, S., Luévanos-Rojas, A. and Medina-Elizondo, M., Optimal dimensioning for the corner combined footings. Advances in Computational Design, 2(2), pp. 169-183, 2017. DOI: https://doi.org/10.12989/acd.2017.2.2.169
- [23] Luévanos-Rojas, A., López-Chavarría, S. and Medina-Elizondo, M., Optimal design for rectangular isolated footings using the real soil pressure. Ingeniería e Investigación, 37(2), pp. 25-33, 2017. DOI: https://doi.org/10.15446/ing.investig.v37n2.61447
- [24] Gandomi, A.H. and Kashani, A.R., Construction cost minimization of shallow foundation using recent swarm intelligence techniques. IEEE Transactions on Industrial Informatics, 14(3), pp. 1009-1106, 2018. DOI: https://doi.org/10.1109/TII.2017.2776132
- [25] Velázquez-Santillán, F., Luévanos-Rojas, A., López-Chavarría, S., Medina-Elizondo, M. and Sandoval-Rivas, R., Numerical

experimentation for the optimal design for reinforced concrete rectangular combined footings. Advances in Computational Design, 3(1), pp. 49-69, 2018. DOI: https://doi.org/10.12989/acd.2018.3.1.049

- [26] Jelusic, P. and Zlender, B., Optimal design of pad footing based on MINLP optimization. Soils and Foundations, 58(2), pp. 277-289, 2018. DOI: https://doi.org/10.1016/j.sandf.2018.02.002
- [27] Malapur, M.M., Cholappanavar, P. and Fernandes, R.J., Optimization of reinforced concrete column and footings using genetic algorithm. International Research Journal of Engineering and Technology (IRJET), 5(8), pp. 546-552, 2018.
- [28] Rawat, S. and Mital, R.K., Optimization of eccentrically loaded reinforced-concrete isolated footings. Practice Periodical on Structural Design and Construction, 23(2), 2018. DOI: https://doi.org/10.1061/(ASCE)SC.1943-5576.0000366
- [29] Nigdeli, S.M., Bekdas, G. and Yang, X-S., Metaheuristic optimization of reinforced concrete footings. KSCE Journal of Civil Engineering, 22(11), pp. 4555-4563, 2018. DOI: https://doi.org/10.1007/s12205-018-2010-6
- [30] Luévanos-Rojas, A., A mathematical model for dimensioning of footings rectangular. ICIC Express Letters Part B: Applications, 4(2), pp. 269-274, 2013.
- [31] Luévanos-Rojas, A., A mathematical model for dimensioning of footings square. International Review of Civil Engineering (IRECE), 3(4), pp. 346-350, 2012.
- [32] Luévanos-Rojas, A., A mathematical model for the dimensioning of circular footings. Far East Journal of Mathematical Sciences, 71(2), pp. 357-367, 2012.
- [33] Luévanos-Rojas, A., A Mathematical model for the dimensioning of combined footings of rectangular shape. Revista Técnica de la Facultad de Ingeniería Universidad del Zulia, 39(1), pp. 3-9, 2016.
- [34] Luévanos-Rojas, A., A new mathematical model for dimensioning of the boundary trapezoidal combined footings. International Journal of Innovative Computing, Information and Control, [online]. 11(4), pp. 1269-1279, 2015. Available at: http://www.ijicic.org/ijicic-110411.pdf
- [35] Luévanos-Rojas, A., López-Chavarría, S. and Medina-Elizondo, M., A new model for T-shaped combined footings. Part I: optimal dimensioning. Geomechanics and Engineering, 14(1), pp. 51-60, 2018. DOI: https://doi.org/10.12989/gae.2018.14.1.051
- [36] Aguilera-Mancilla, G., Luévanos-Rojas, A., López-Chavarría, S. and Medina-Elizondo, M., Modeling for the strap combined footings. Part I: optimal dimensioning. Steel and Composite Structures, 30(2), pp. 97-108, 2019. DOI: https://doi.org/10.12989/scs.2019.30.2.097

**M. García-Galván**, received a MSc. in International Business Law in 2002 from the ITESM in Monterrey Campus, and the PhD in Administration and Senior Management in 2018, from the Facultad de Contaduría y Administración of the Universidad Autónoma de Coahuila, Torreón, Coahuila, Mexico. She is professor and researcher of the Universidad Autónoma de Coahuila (2018-Current). His research interests are mathematical models applied to Administration. She has 5 papers published in international scientific research Journals. ORCID: 0000-0001-8854-0930

A. Luévanos-Rojas, received his BSc. in Civil Engineering in 1981, his MSc. in Planning and Construction in 1996, and the PhD Engineering in Planning and Construction in 2009, all of them from the Facultad de Ingeniería, Ciencias y Arquitectura of the Universidad Juárez del Estado de Durango, Gómez Palacio, Durango, México. He received the MSc in Structures in 1983, from the Escuela Superior de Ingeniería y Arquitectura the Instituto Politécnico Nacional, Distrito Federal, México. Also, he received the MSc. in Administration in 2004, from the Facultad de Contaduría y Administración of the Universidad Autónoma de Coahuila, Torreón, Coahuila, Mexico. He is professor and researcher of the Universidad Autónoma de Coahuila (2015-Current). He has more than 100 papers published in international scientific research Journals. His research interests include: mathematical models applied to structures. He is a member of the National System of Researchers of Mexico.

**S. López-Chavarría**, received his BSc. in Public Accountant, his MSc. in Administration, and the PhD in Administration and Senior Management from the Facultad de Contaduría y Administración of the Universidad Autónoma de Coahuila, Torreón, Coahuila, Mexico. She is professor and researcher of the Universidad Autónoma de Coahuila (2000-Current). His research interests include: mathematical models applied to structures, methods of structural analysis, design of concrete and steel structural members, and analysis of non-prismatic members. She has more than 50 papers published in national and international scientific research Journals. She has been a speaker at scientific meetings in España, Colombia, Argentina. She is a member of the National System of Researchers of Mexico.

ORCID: 0000-0001-8909-1794

**M. Medina-Elizondo**, received his BSc. in Public Accountant, his MSc. in Administration from the Facultad de Contaduría y Administración of the Universidad Autónoma de Coahuila, Torreón, Coahuila, Mexico. He received the PhD in Administration Sciences from the Universidad Nacional Autónoma de México, Distrito Federal, Mexico. Also, he received the PhD in Administration Sciences from the Universidad Vatónoma de México. He received the PhD in Administration Sciences from the Universidad de Newport, U.S.A. He is professor and researcher of the Universidad Autónoma de Coahuila (1988-Current). His research interests include: mathematical models applied to structures, methods of structural analysis, design of concrete and steel structural members, and analysis of non-prismatic members. He has more than 80 papers published in national and international scientific research Journals.

ORCID: 0000-0002-6113-4964

**J.B. Rivera-Mendoza**, received a MSc. in Business Administration in 1985, and the PhD in Administration and Senior Management in 2018, from the Facultad de Contaduría y Administración of the Universidad Autónoma de Coahuila, Torreón, Coahuila, Mexico. He is professor and researcher of the Universidad Autónoma de Coahuila (2018-Current). His research interests are mathematical models applied to Administration. He has 5 papers published in international scientific research Journals. ORCID: 0000-002-0514-0796